



Liebert ITON 1000

Power Availability

KEEPS IT ON : A Reliable Power Protection And Backup Solution For Your PC



ITON



Features :

- Auto Sleep Mode
- Insta Restart
- Power protection for Fax/Modem
- Smart Monitoring Software
- Smart Microprocessor control
- Smart AVR Technology
- Communication Port
- Overload Protection and alarm



WE HELP YOU GET IT RIGHT - RIGHT FROM THE START.

Liebert ITON 1000

Power Availability

Specifications

ITON 1000

MODEL	ITON 1000		
CAPACITY	VA/W	1000VA/600W	
INPUT	Voltage Range	160-270V	
	Frequency	45-65 Hz (Auto sensing)	
OUTPUT	Voltage	230V	
	Voltage Regulation (Batt. Mode)	+/- 5%	
	Frequency	50Hz or 60Hz	
	Frequency Regulation (Batt. Mode)	+/- 1Hz	
	Output Waveform	Stepped Waveform	
BATTERY	Overload	110% for 5 minutes as "Mains" mode	
	Battery Type & Number	12V/7AH – 2 Pcs	
	Backup Time* (As per the loads)	30 min typical* (with 1 PC)	
	Recharge Time	8 hours to 90% after complete discharge	
TRANSFER TIME	Typical	4-6 ms	
INDICATOR (LED Bar Graph)	AC Mode	Green Lighting	The 1 st green lighting; The 2 nd to 5 th green gradually lighting indicating load capacity
	Backup Mode	Green flashing	The 1 st green flashing; The 2 nd to 5 th green gradually lighting indicating batteries capacity
	Fault		The red lighting
AUDIBLE ALARM	Backup Mode		Sounding every 10 seconds
	Low Battery		Sounding every second
	Overload		Sounding every 0.5 seconds
	Battery Replacement		Sounding every 2 seconds
	Fault		Continuously Sounding
PROTECTION	Full Protection		Discharge, overcharge, and overload protection
PHYSICAL	Dimension (mm), DxWxH		369x141x181
	Net Weight		13.5 kg
ENVIRONMENT	Operating Environment		0-40 C, 0-90% relative humidity (non-condensing)
	Noise Level		Less than 40 dB
INTERFACE	RS-232		Support Windows 98/NT/ME/2000/2003/XP, Linux, HP-UX, IBM AIX, Sun Solaris, Unixware, Free BSD, Mac OS and Compaq True

*For details on backup time contact our authorised representative.

While every precaution has been taken to ensure accuracy and completeness in this brochure, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.

© 2002 Liebert Corporation. All right reserved throughout the world. Specifications subject to change without notice.

All names referred to are trademarks or registered trademarks of their respective owners.

QS - BR - PRD - 1 - 01 - 00

LIEBERT CORPORATION

1050, DEARBORN DRIVE, P. O. BOX: 29186
COLUMBUS, OHIO - 43229.
TEL.: 800.877.9222 (U.S & CANADA ONLY)
TEL.: 614.888.0246 (OUTSIDE U.S.)
FAX: 614.841.6022.

COUNTRY OFFICE

EMERSON NETWORK POWER (INDIA) PRIVATE LTD.
PLOT NO. C-20, ROAD NO. 19, WAGLE ESTATE,
THANE (W), MAHARASHTRA - 400 604. INDIA.
TEL.: 91-22-25807000/ 2388.
FAX: 91-22-25828358.

CITY OFFICES

West Zone

Mumbai : 022-25002318/2294
Pune : 020-25676975/0709
Baroda : 0265-2314296/2330383
Nagpur : 0712-2548551
Indore : 0731-2203806

East Zone

Kolkata : 033-22890492/93/1272/1273
Jamshedpur : 0657-2227678
Guwahati : 0361-2453270
Bhubaneswar : 0674-2520778

North Zone

New Delhi : 011-25824206/08
Chandigarh : 0172-5077531
Lucknow : 0522-2237174

South Zone

Bangalore : 080-51135670/770/870
Secunderabad : 040-27810957/27811619
Cochin : 0484-2341985/86
Chennai : 044-28151063/28152596



Voice of Customers UPS Awards 2004-05 for Product Line & Customer Service Awards in IT, Telecom, Large Enterprise & Hospitals and Customer Service Leadership Award in BFSI



Best IT Hardware Company
Maharashtra IT Award 2004-05



Emerson Among Top 50
On Fortune Survey Of
"Worlds Most Admired"
Companies.



EMERSON NETWORK POWER WEB SITE
<http://www.emersonnetworkpower.co.in>

